Dual Socket AC EV Charger

7.4kW x2 / 22kWx2











Emergency Button Switch

Electric Leakage Test Button

Type 2 Socket

Logo

LCD Screen

RFID

LED Light

Product Overview

Elevate your charging experience with the Beny Dual Socket AC EV charger, certified by reputable associations. It's engineered for intelligence, reliability, convenience, and efficiency. Take charge of your charger through a smart app and multiple connectivity options. Enjoy seamless interaction with a 5.0-inch touch screen interface.

Product Advantages



5.0-inch Touch Screen



0CPP 1.6J









IP55 Rating

T2S AC EV Charger

Model Selection

Dual Socket AC EV Charger	BCPC-B2N-P	BCPC-BT2N-P	BCPC-D2N-P	BCPC-DT2N-P
				0
Maximum Power	7.4kW	22kW	2x7.4kW	2x22kW
Input Voltage /Output voltage	AC230 1-Phase	AC400 3-Phase	AC230 1-Phase	AC400 3-Phase
Input Frequency	50/60Hz			
Tethered/Socket	Socket			
Meter	MID I	Meter	2xMID Meter	
Display	LCD Screen+LED Lights			
RFID	Ø	Ø	Ø	Ø
DLB	0	0	0	0
Wi-Fi	Ø	Ø	Ø	Ø
Ethernet	⊘	Ø	Ø	Ø
Bluetooth	Ø	Ø	Ø	⊘
4G	0	0	0	0
Over Voltage &Under Voltage Protection	Ø	Ø	Ø	Ø
Emergency Stop	Ø	Ø	Ø	Ø
Over Current Protection	Ø	Ø	Ø	Ø
CP Signal Short Circuit Protection	Ø	Ø	⊘	Ø
Over Temperature Protection	Ø	Ø	Ø	⊘
Lightning Protection	Ø	Ø	Ø	⊘
Contactor Adhesion Protection	Ø	Ø	Ø	Ø
Protection Degree	IP55	IP55	IP55	IP55
Environment Temperature	-25°C-+50°C			
Maximun Altitude	<2000m			



